



No	L	CABLE
DW-U5E-0025-YL	250 ± 40mm	CAT. 5E/UTP 26AWG, YELLOW
DW-U5E-005-YL	500 ± 40mm	CAT. 5E/UTP 26AWG, YELLOW
DW-U5E-010-YL	1000 ± 40mm	CAT. 5E/UTP 26AWG, YELLOW
DW-U5E-020-YL	2000 ± 40mm	CAT. 5E/UTP 26AWG, YELLOW

- NOTES:
1. ELECTRICAL TEST: 100% OPEN, SHORT & MISS WIRE TEST.
 2. CONDUCTOR RESISTANCE: 5 OHM MAX
 3. INSULATOR RESISTANCE: DC300V/0.01S 500K OHM MIN.
 4. PRINTING WORD OF CABLE;

NO	PART NAME	DESCRIPTION	QTY
3	Cable	CAT. 5E/UTP CABLE 26AWG(7/0.16)*4P, JACKET: PVC, YELLOW; OD:5.3 ± 0.2mm	1
2	Molding	45P PVC OUTER MOLDING HOUSING, COLOR:YELLOW	2
1	Connector	RJ45 MALE CONNECTOR, PIN GOLD PLATED 3U".	2

-TOLERANCES- UNLESS OTHERWISE SPECIFIED						
	PART DESCRIPTION: Patch Cable CAT5E UTP PVC 0,25m Yellow Non-Snag-Proof					
UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE: 0.5 - 8mm ± 0.20mm 8 - 30mm ± 0.25mm 30 - 120mm ± 0.30mm	Appd: JIM.KING	P/N: DW-U5E-0025-YL				
	Check:	Date	Scale	Unit	Type	Page
	Draw: Gavin	2022.11.30	Free	MM	Z	1/1