



No	L	CABLE
DW-F6A-0025-YL	250 ± 40mm	CAT. 6A/FTP 26AWG, YELLOW
DW-F6A-005-YL	500 ± 40mm	CAT. 6A/FTP 26AWG, YELLOW
DW-F6A-010-YL	1000 ± 40mm	CAT. 6A/FTP 26AWG, YELLOW
DW-F6A-020-YL	2000 ± 40mm	CAT. 6A/FTP 26AWG, YELLOW

- NOTES:
1. ELECTRICAL TEST: 100% OPEN, SHORT & MISS WIRE TEST.
 2. CONDUCTOR RESISTANCE: 5 OHM MAX
 3. INSULATOR RESISTANCE: DC300V/0.01S 500K OHM MIN.
 4. PRINTING WORD OF CABLE

3	Cable	CAT. 6A/FTP CABLE 26AWG (7/0.16)*4P+AL+D (7/0.12BS) JACKET: PVC, YELLOW; OD: 6.0 ± 0.2mm	1
2	Molding	45P PVC OUTER MOLDING HOUSING, COLOR: YELLOW	2
1	Connector	RJ45 MALE CONNECTOR (SHIELD), PIN GOLD PLATED 3U".	2
NO	PART NAME	DESCRIPTION	QTY

-TOLERANCES- UNLESS OTHERWISE SPECIFIED						
	PART DESCRIPTION: Patch Cable CAT6A FTP PVC 0.5m Yellow Non-Snag					
UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE: 0.5 - 8mm ± 0.20mm 8 - 30mm ± 0.25mm 30 - 120mm ± 0.30mm	Appd:	JIM. KING				
	Check:	Date:	Scale:	Unit:	Type:	Page:
Draw:	Gavin	2022.11.22	Free	MM	Z	1/1

1

2

3

4

5

6