



No	L	CABLE
DW-F6A-0025-GR	250 ± 40mm	CAT. 6A/FTP 26AWG, GREY
DW-F6A-005-GR	500 ± 40mm	CAT. 6A/FTP 26AWG, GREY
DW-F6A-010-GR	1000 ± 40mm	CAT. 6A/FTP 26AWG, GREY
DW-F6A-020-GR	2000 ± 40mm	CAT. 6A/FTP 26AWG, GREY
DW-F6A-030-GR	3000 ± 40mm	CAT. 6A/FTP 26AWG, GREY

- NOTES:
 1. ELECTRICAL TEST: 100% OPEN, SHORT & MISS WIRE TEST.
 2. CONDUCTOR RESISTANCE: 5 OHM MAX
 3. INSULATOR RESISTANCE: DC300V/0.01S 500K OHM MIN.
 4. PRINTING WORD OF CABLE

NO	PART NAME	DESCRIPTION	QTY
3	Cable	CAT. 6A/FTP CABLE 26AWG (7/0.16)*4P+AL+D(7/0.12BS) JACKET: PVC, GREY; OD: 6.0 ± 0.2mm	1
2	Molding	45P PVC OUTER MOLDING HOUSING, COLOR: GREY	2
1	Connector	RJ45 MALE CONNECTOR (SHIELD), PIN GOLD PLATED 3U".	2

-TOLERANCES- UNLESS OTHERWISE SPECIFIED						
	PART DESCRIPTION: Patch Cable CAT6A FTP PVC 0,5m Gray Non-Snag-Proof					
UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE: 0.5 - 8mm ± 0.20mm 8 - 30mm ± 0.25mm 30 - 120mm ± 0.30mm	Appd: JIM.KING	P/N: DW-F6A-005-GR				
	Check:	Date	Scale	Unit	Type	Page
Draw: Gavin		2022.11.30	Free	MM	Z	1/1