



SPECIFICATIONS:

1 Electrical Specification:

- A.Rated Voltage 150V AC;Rated Current 1.5A
- B.Withstand Voltage: <0.5A,1000V DC/1Minute.
- C.Insulation Resistance: 1000VDC/1Minute, >500 Ω
- D.Contact Resistance: <20mΩ

2 Mechanical Features:

- A.Pull Testing -Cable, socket tensile strength at least 20 LBS a minute (89N)
- B.Endurance Testing ->750 plug and unplug tests.

3 Temperature Range: -40°C~+85°C

4 Environmental Protection:

- A.Products comply with RoHS,REACH and other environmental specifications

No.	PART NAME	DESCRIPTION	Q'TY
2	PIN	Brass, Gold plated	1
1	Housing	PC,White	1

<p>-TOLERANCES- UNLESS OTHERWISE SPECIFIED</p> <p>UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE: 0.5 - 8mm ± 0.20mm 8 - 30mm ± 0.25mm 30 -120mm ± 0.30mm</p>						
			<p>PART DESCRIPTION: RJ45 CAT5E 8p8c 1.1mm Shielded with Grounding Buckle for Solid/Stranded Wire</p>			
	<p>Appr: JIM.KING</p>		<p>P/N: DW-CO-RJ45-5-FTP-GB-EASY</p>			
	<p>Check:</p>	<p>Date</p>	<p>Scale</p>	<p>Unit</p>	<p>Type</p>	<p>Page</p>
<p>Draw: XIEFENG</p>	<p>2023.03.30</p>	<p>Free</p>	<p>MM</p>	<p>Z</p>	<p>1/1</p>	