



No	L	CABLE
DW-F6A-0025-GR	250 ± 40mm	CAT. 6A/FTP 26AWG, GREY
DW-F6A-005-GR	500 ± 40mm	CAT. 6A/FTP 26AWG, GREY
DW-F6A-010-GR	1000 ± 40mm	CAT. 6A/FTP 26AWG, GREY
DW-F6A-020-GR	2000 ± 40mm	CAT. 6A/FTP 26AWG, GREY
DW-F6A-030-GR	3000 ± 40mm	CAT. 6A/FTP 26AWG, GREY

NOTES:

- ELECTRICAL TEST: 100% OPEN, SHORT & MISS WIRE TEST.
- CONDUCTOR RESISTANCE: 5 OHM MAX
- INSULATOR RESISTANCE: DC300V/0.01S 500K OHM MIN.
- PRINTING WORD OF CABLE

NO	PART NAME	DESCRIPTION	QTY
3	Cable	CAT. 6A/FTP CABLE 26AWG(7/0.16)*4P+AL+D(7/0.12BS) JACKET: PVC, GREY; OD: 6.0 ± 0.2mm	1
2	Molding	45P PVC OUTER MOLDING HOUSING, COLOR: GREY	2
1	Connector	RJ45 MALE CONNECTOR (SHIELD), PIN GOLD PLATED 3U".	2
NO	PART NAME	DESCRIPTION	QTY

<p>-TOLERANCES- UNLESS OTHERWISE SPECIFIED</p>						
	<p>PART DESCRIPTION: Patch Cable CAT6A FTP PVC 3m Gray Non-Snag-Proof</p>					
<p>UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE:</p> <p>0.5 - 8mm ± 0.20mm 8 - 30mm ± 0.25mm 30 - 120mm ± 0.30mm</p>	<p>Appd: JIM.KING</p>	<p>P/N: DW-F6A-030-GR</p>				
	<p>Check:</p>	Date	Scale	Unit	Type	Page
	<p>Draw: Gavin</p>	2022.11.30	Free	MM	Z	1/1