



| | | |
|---|--------------------------------|--|
| 9 | Ex-factory parts | Installation manual |
| 8 | Protection control module | Double break switch + lightning protection |
| 7 | Socket system | 8-bit French |
| 6 | Terminal box | |
| 5 | Cable specification | 1.5 ² mm , 3 m wire European plug |
| 4 | Angle of hanging ear | Mounting ears are installed at 0° |
| 3 | Fixed hole center distance | 466±3mm |
| 2 | Product size and specification | 488*44.8*45 |
| 1 | Shell material and color | 1U profile, black |

| | | | | | | |
|---|--|------------------|-------|------|------|------|
| -TOLERANCES- UNLESS OTHERWISE SPECIFIED | | | | | | |
| | PART DESCRIPTION: DATAWAY PDU 19" with surge protection 8x 230V, 1U, M6 set, 3m, LED | | | | | |
| UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE: 0.5 - 8mm ± 0.20mm 8 - 30mm ± 0.25mm 30 - 120mm ± 0.30mm | Appr: JIM.KING | P/N: PDU-8-SP-3M | | | | |
| | Check: | Date | Scale | Unit | Type | Page |
| | Draw: XIEFENG | 2023.05.09 | Free | MM | Z | 1/1 |