



No	L	CABLE
DW-F5E-0025-YL	250 ± 40mm	CAT. 5E/FTP 26AWG, YELLOE
DW-F5E-005-YL	500 ± 40mm	CAT. 5E/FTP 26AWG, YELLOE
DW-F5E-010-YL	1000 ± 40mm	CAT. 5E/FTP 26AWG, YELLOE
DW-F5E-020-YL	2000 ± 40mm	CAT. 5E/FTP 26AWG, YELLOE

NOTES:

1. ELECTRICAL TEST: 100% OPEN, SHORT & MISS WIRE TEST.
2. CONDUCTOR RESISTANCE: 10 OHMS MAX.
3. INSULATOR RESISTANCE: 5M OHMS MIN, DC 300V 0.01sec.
4. HI-POT: DC 300V 0.1sec.

NO	PART NAME	DESCRIPTION	QTY
3	Cable	CAT. 5E/FTP CABLE 26AWG (7/0.16)*4P+AL+D(7/0.12BS) JACKET: PVC, YELLOW; OD: 5.5 ± 0.2mm	1
2	Molding	45P PVC OUTER MOLDING HOUSING, COLOR: YELLOW	2
1	Connector	RJ45 MALE CONNECTOR (SHIELD), PIN GOLD PLATED 3U".	2

-TOLERANCES- UNLESS OTHERWISE SPECIFIED							
UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE: 0.5 - 8mm ± 0.20mm 8 - 30mm ± 0.25mm 30 - 120mm ± 0.30mm		PART DESCRIPTION: Patch Cable CAT5E FTP PVC 2m Yellow Non-Snag-Proof		P/N: DW-F5E-020-YL			
		Appd: JIM KING	Check:	Date	Scale	Unit	Type
Draw: Gavin		2022.11.30	Free	MM	Z	1/1	