



| No | L | CABLE |
|----------------|-------------|------------------------|
| DW-U5E-0025-RD | 250 ± 40mm | CAT. 5E/UTP 26AWG, RED |
| DW-U5E-005-RD | 500 ± 40mm | CAT. 5E/UTP 26AWG, RED |
| DW-U5E-010-RD | 1000 ± 40mm | CAT. 5E/UTP 26AWG, RED |
| DW-U5E-020-RD | 2000 ± 40mm | CAT. 5E/UTP 26AWG, RED |

NOTES:
 1. ELECTRICAL TEST: 100% OPEN, SHORT & MISS WIRE TEST.
 2. CONDUCTOR RESISTANCE: 5 OHM MAX
 3. INSULATOR RESISTANCE: DC300V/0.01S 500K OHM MIN.
 4. PRINTING WORD OF CABLE;

| NO | PART NAME | DESCRIPTION | QTY |
|----|-----------|---|-----|
| 3 | Cable | CAT. 5E/UTP CABLE 26AWG(7/0.16)*4P, JACKET: PVC, RED; OD: 5.3 ± 0.2mm | 1 |
| 2 | Molding | 45P PVC OUTER MOLDING HOUSING, COLOR: RED | 2 |
| 1 | Connector | RJ45 MALE CONNECTOR, PIN GOLD PLATED 3U". | 2 |

| | | | | | |
|---|----------------|------------|---|-------|------|
| -TOLERANCES- UNLESS OTHERWISE SPECIFIED | | | | | |
| UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE: 0.5 - 8mm ± 0.20mm 8 - 30mm ± 0.25mm 30 - 120mm ± 0.30mm | | | PART DESCRIPTION: | | |
| | Appd: JIM.KING | | Patch Cable CAT5E UTP PVC 2m Red Non-Snag-Proof | | |
| | Check: | | Date | Scale | Unit |
| Draw: Gavin | | 2022.11.30 | Free | MM | Z |