


Item no.	57064614-01		Connector type	5/8MU-TL646 PIN Ø.1,8x47MM	
			For cable	Belden Coax3 FOAM FB20	
Frequency Range	0.3 - 3000 MHz		Product photo		
Impedance (Nom.)	75 Ω				
Amp. Rating (measured)	17.0 A @10°C increase				
(calculated)	24.0 A @20°C increase				
Transfer Impedance (CoMeT)	Class A++				
	<0.9 mΩ/m @ 5-30MHz				
	<0.12 mΩ/item @ 5-30MHz				
Screening Attenuation(CoMeT)	Class A+				
	>95 dB @ 30-1000MHz				
	>95 dB @ 1000-2000MHz				
	>80 dB @ 2000-3000MHz				
Return Loss (IEC 61169-1)	Better than	Typical	Insertion Loss Max.	Better than	Typical
0.3 - 500 MHz	-35 dB	-37.6 dB	0.3 - 500 MHz	-0.11 dB	-0.06 dB
500 - 860 MHz	-35 dB	-37.6 dB	500 - 860 MHz	-0.13 dB	-0.08 dB
860 - 1000 MHz	-35 dB	-37.6 dB	860 - 1000 MHz	-0.14 dB	-0.09 dB
1000 - 1750 MHz	-30 dB	-32.7 dB	1000 - 1750 MHz	-0.18 dB	-0.13 dB
1750 - 2150 MHz	-28 dB	-31.0 dB	1750 - 2150 MHz	-0.19 dB	-0.14 dB
2150 - 3000 MHz	-27 dB	-30.4 dB	2150 - 3000 MHz	-0.24 dB	-0.19 dB
Temperature Installing	-5° to +50° C		Intermodulation 3rd Order (@2x+37dBm)	IM3 -125 dBc	
Operating	-40° to +70° C		Inner Conductor Resistance (@ 1 A DC)	<0.9 mΩ	
Storing	-40° to +70° C		Insulation Resistance (@ 500 VDC)	>200 GΩ	
Sealing Test (IEC IP-code)	IP X8 10 meter / 8 hours		Dielectric Strength DC Test Voltage	>3.5 KV	
O-rings	EPDM		Max. Tensile Strength Overall	>1500 N	
Base Material	Brass CuZn39Pb3		Inner Conductor	>500 N	
Body Parts	Brass CuZn39Pb3		Torsional Strength (Connector / Cable)	>4.0 Nm	
Inner Conductor	Brass CuZn39Pb3		Test performed by	Søren B. Sørensen	
Plating	Nitin-6		Date of release	September 22, 2014	
Body Parts	Nitin-6				
Inner Conductor	Nitin-6				
Insulators	COC (Topas) / PP with Glass				
Remarks					

All tests performed using instruments calibrated in accordance to our ISO 9001 certification. Further technical specifications and installation instructions can be obtained on request.