

Item no.	87455510	Connector type	IEC14M-FF ACCEPTS PIN Ø 0.5-1.2mm

Frequency Range	0.3 - 3000 MHz
Impedance (Nom.)	75 Ω
Amp. Rating (measured)	3,0 Cable data
(calculated)	4,2 Cable data
Transfer Impedance (CoMeT)	<0,9 mΩ/m @ 5-30MHz
	<0,03 mΩ/con. @ 5-30MHz
Shielding Effectiveness (CoMeT)	>130 dB @ 30-1000MHz
	>130 dB @ 1000-3000MHz



All tests performed using instruments calibrated in accordance to our ISO 9001 certification. Further technical specifications and installation instructions can be obtained on request.

Return Loss (IEC 61169-1)
(Rhode und Schwarz ZVB-8)

	Better than	Typical
0.3 - 500 MHz	-25 dB	-28,1 dB
500 - 860 MHz	-20 dB	-23,3 dB
860 - 1000 MHz	-19 dB	-21,8 dB
1000 - 1750 MHz	-14 dB	-16,7 dB
1750 - 2150 MHz	-12 dB	-15,2 dB
2150 - 3000 MHz	-12 dB	-14,9 dB

Insertion Loss Max.

	Better than	Typical
0.3 - 500 MHz	-0,13 dB	-0,08 dB
500 - 860 MHz	-0,14 dB	-0,09 dB
860 - 1000 MHz	-0,15 dB	-0,10 dB
1000 - 1750 MHz	-0,19 dB	-0,14 dB
1750 - 2150 MHz	-0,22 dB	-0,17 dB
2150 - 3000 MHz	-0,25 dB	-0,20 dB

Temperature

Installing	-5° to +50° C
Operating	-40° to +70° C
Storing	-40° to +70° C

Intermodulation

3rd Order (@2x0,5W)	IM3	IP3-value
	-157 dBc	105 dBm

Inner Conductor Resistance

(@ 1 A DC)	0,4 mΩ
------------	--------

Sealing Test

(IEC IP-code)	IP X8 30 meter / 8 hours
---------------	--------------------------

Insulation Resistance

(@ 500 VDC)	>200 GΩ
-------------	---------

O-rings

EPDM

Dielectric Strength

DC Test Voltage	4,0 KV
-----------------	--------

Base Material

Body Parts	Brass CuZn39Pb3
Inner Conductor	Tin Bronze BZ4

Plating

Body Parts	Nitin-6
Inner Conductor	Nitin-6

Insulators

PP with Glass

Test performed by

Sven-Erik Sandberg

Date of release

May 02, 2011

Remarks

ISO 9001:2008 / ISO 14001 certified

Distributor:

CABELCON
connectors

Corning Cabelcon ApS, Industriparken 10, DK 4760 Vordingborg
Tel: +45 55 98 55 99 · Fax: + 45 55 98 55 04
E-mail: cabelcon@cabelcon.dk · www.cabelcon.dk